


## Technical Data Sheet

# BIVOS Oil Wax No. 375

<b>Range of application</b>	For interior timber after pre-treatment with LIVOS products. For maintaining previously waxed or oiled timber; for restoration of old furniture or wood carvings. For the care of KERA Cotto and linoleum.
<b>Technical qualities</b>	Transparent, velvet gloss, moisture-resistant, antistatic finish. DIN EN 71 Part 3 certified.
<b>Full declaration</b>	 <p>All LIVOS products have been developed according to a holistic criteria catalogue and also meet health and ecological criteria. They have been thoroughly tested for beneficial working qualities. The products contents of our products are fully declared. LIVOS consequent sustainable and resource sparing production is confirmed by certification of ARGE kdR e. V.</p>
<b>Color</b>	Clear. Tinting is possible by adding a max. of 10% of VINDO Natural Gloss Paint No. 629.
<b>Dilution</b>	Delivered ready to use.
<b>Application method</b>	Spraying, or with a wadded cloth.
<b>Coverage</b>	1 liter (1.06 fl. quart.) is sufficient for approximately 100 m <sup>2</sup> (1076 ft <sup>2</sup> ), i.e. 10 ml/m <sup>2</sup> , when applying with a wadded cloth and pre-treated surfaces. 1 liter (1.06 fl. quart.) is sufficient for up to 167 m <sup>2</sup> (1800 ft <sup>2</sup> ), i.e. 6 ml/m <sup>2</sup> , for other modes of application. Coverage could be considerably less depending on the condition and absorbency of the surface. Always do a test application!
<b>Drying time</b>	Application with a wadded cloth approximately 20 – 30 minutes at 23°C and 50% relative humidity. A drying time of 30 – 120 minutes is required when applying by spraying device. All other application methods 24 hrs.
<b>Cleaning up</b>	Clean equipment immediately after use with SVALOS Thinner No. 222, or LEVO Brush Cleaner No. 997.
<b>Specific gravity</b>	0.84 g/ml.
<b>Safety advice</b>	<p>Always be sure to store and dispose cleaning cloths, polishing pads, sponges, etc. that are still wet or even slightly moist with BIVOS-Oil-Wax No. 375 in an airtight metal container or in water, as there is a danger of spontaneous combustion caused by the vegetable oil content in the product.</p> <p>The product alone will not undergo spontaneous combustion. Contains limonene. S 2      Keep out of the reach of children S 62     If swallowed do not induce vomiting; Seek medical advice immediately and show the container or label.</p>
<b>Disposal</b>	According to locally regulated laws.
<b>Container Size</b>	0.05 lt; 0.125 lt; 0.25 lt; 0.75 lt; 2.5 lt; 10 lt; 30 lt; 200 lt.
<b>Storage</b>	Cool and dry please see label for expiry date. Close lid tightly after use, transfer unused portion of product to a smaller container for storage.  See reverse for Application Instructions.

## How to use

# BIVOS Oil Wax No. 375

- Preparation** The surface must be dry, solid, clean, and free of grease and dust. Pretreat timber with LIVOS oils or stains like MELDOS Natural Resin Hardening Oil No. 264, ARDVOS Universal Wood Oil No. 266, GORMOS Wax Oil No. 267 or DARIX Transparent Furniture Stain No. 297.
- Application** Stir or shake product thoroughly before using. Apply very thin; it is best to use a cloth to rub the product in vigorously. Polishing the surface after treatment is not necessary. With other application methods such as spraying, careful attention must be paid to applying a very thin and even coat. Excess product should be removed with a cloth. After 20 - 30 minutes drying time, polish surface with a brush or a clean cloth. 1 - 2 hours after polishing, surface can be touched. **Industrial application:** via spraying and brush techniques (please request technical advice if necessary).
- Renovation** Pre-treat the surface with the recommended LIVOS products, then apply BIVOS Oil Wax No. 375. Always test for compatibility with existing surface coatings before use.

**These directions are the result of long years of research and practical testing. They are backed by our most current expert information. New findings may invalidate this information. This data sheet is meant to serve as information and instruction. No legal liability should be interpreted from it. In case of doubt, please contact the retailer, wholesaler, or manufacturer.**